

**Revision Number: 008.2** Issue date: 07/17/2018

## 1. PRODUCT AND COMPANY IDENTIFICATION

LOCTITE T70 known as T70 THINNER IDH number: **Product name:** 510030

**1GA BOTTLE** 

Product type: Cleaner Item number: M00307 Restriction of Use: None identified Region: **United States** 

Company address: **Contact information:** 

Henkel Corporation Telephone: +1 (860) 571-5100

One Henkel Way MEDICAL EMERGENCY Phone: Poison Control Center Rocky Hill, Connecticut 06067 1-877-671-4608 (toll free) or 1-303-592-1711

TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

# 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

DANGER: ASPIRATION HAZARD IF SWALLOWED.

HIGHLY FLAMMABLE LIQUID AND VAPOR.

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

CAUSES SERIOUS EYE IRRITATION.

MAY CAUSE DROWSINESS OR DIZZINESS.

CAUSES DAMAGE TO ORGANS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	2
EYE IRRITATION	2A
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
ASPIRATION HAZARD	1





### **Precautionary Statements**

Prevention:

Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment. Use non-sparking tools. Take action to prevent static discharges. Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye protection, and face protection.

IDH number: 510030 Product name: LOCTITE T70 known as T70 THINNER 1GA BOTTLE Page 1 of 6

Response:

IF SWALLOWED: Immediately call a physician or poison control center. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed: Call a poison center or physician. Do NOT induce vomiting. If eye irritation persists: Get medical attention. In case of

fire: Use foam, dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place.

Keep cool. Store locked up.

Disposal:

Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
2-Propanol	67-63-0	40 - 50
Methanol	67-56-1	40 - 50

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections

#### 4. FIRST AID MEASURES

**Inhalation:** Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. If symptoms develop and persist, get medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately flush skin with

plenty of water (using soap, if available). If symptoms develop and persist, get

medical attention. Wash clothing before reuse.

**Eye contact:** Immediately flush eyes with plenty of water for at least 15 minutes. Get

medical attention.

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious

person. Get medical attention.

Symptoms: See Section 11.

#### 5. FIRE FIGHTING MEASURES

**Extinguishing media:** Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: Closed containers may rupture (due to build up of pressure) when exposed to

extreme heat. Vapors may travel considerable distance to source of ignition

and flash back.

Hazardous combustion products: Oxides of carbon. Thermal decomposition can lead to release of irritating

gases and vapors.

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

Clean-up methods: Ventilate area. Remove all sources of ignition. Evacuate personnel to safe

areas. Wear suitable protective clothing, gloves and eye/face protection. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a partly filled, closed container until disposal. Spilled liquid is combustible and can be ignited by heat, flames, sparks, or other sources of ignition. Refer to Section 8 "Exposure Controls / Personal"

Protection" prior to clean up.

## 7. HANDLING AND STORAGE

**Handling:** Keep away from heat, spark and flame. Keep container closed. Use only with

adequate ventilation. Empty containers retain product residue, so obey hazard

warnings and handle empty containers as if they were full.

Storage: Store away from ignition sources. Store in original container until ready to use.

Keep away from heat, spark and flame.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
2-Propanol	200 ppm TWA 400 ppm STEL	400 ppm (980 mg/m3) PEL	None	None
Methanol	200 ppm TWA (SKIN) 250 ppm STFI	200 ppm (260 mg/m3) PEL	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

showers and eye wash stations should be available.

**Skin protection:**Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:LiquidColor:ColorlessOdor:AlcoholicOdor threshold:Not available.pH:Not applicable

Vapor pressure: 44 mm hg (25 °C (77°F))

Boiling point/range: 82 °C (179.6 °F)

IDH number: 510030 Product name: LOCTITE T70 known as T70 THINNER 1GA BOTTLE Page 3 of 6

Melting point/ range: Not determined

Specific gravity: 0.79

Vapor density:Heavier than air.Flash point:12 °C (53.6 °F)

Flammable/Explosive limits - lower: 2 % Flammable/Explosive limits - upper: 12.7 %

399 °C (750.2 °F) Autoignition temperature: Flammability: Not applicable Evaporation rate: Not available. Solubility in water: Miscible Partition coefficient (n-octanol/water): Not available. **VOC** content: 100 %; 790 g/l Viscosity: 1.0 mPa.s **Decomposition temperature:** Not available.

#### 10. STABILITY AND REACTIVITY

Stability: Stable under recommended storage conditions.

Electrostatic charge may build-up during handling. Grounding of equipment is recommended.

**Hazardous reactions:** None under normal processing.

Hazardous decomposition

products:

IDH number: 510030

Oxides of carbon. Thermal decomposition can lead to release of irritating gases and vapors.

**Incompatible materials:** Strong oxidizing agents. Strong acids and strong bases.

**Reactivity:** Not available.

Conditions to avoid: High temperatures. Heat, flames, sparks and other sources of ignition. Store away from

incompatible materials.

## 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

#### Potential Health Effects/Symptoms

Inhalation: Inhalation of processing fumes may be harmful. Vapor overexposure may cause drowsiness.

Dizziness. Aspiration may cause lung damage.

**Skin contact:** May cause skin irritation.

Eye contact: Causes serious eye irritation. Can cause blindness. Redness. Tearing.

**Ingestion:** This product may be fatal if it is swallowed. Aspiration may occur during swallowing or vomiting,

resulting in lung damage.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
2-Propanol	Oral LD50 (Rat) = 5,045 mg/kg Oral LD50 (Mouse) = 3,600 mg/kg Oral LD50 (Rabbit) = 6,410 mg/kg Oral LD50 (Rat) = 4.7 g/kg Oral LD50 (Mouse) = 4.5 g/kg Oral LD50 (Rabbit) = 8.0 g/kg Oral LD50 (Rabbit) = 5.03 g/kg Dermal LD50 (Rabbit) = 12,800 mg/kg	Allergen, Central nervous system, Irritant
Methanol	Oral LD50 (Rat) = 5,628 mg/kg Oral LD50 (Mouse) = 7,300 mg/kg Oral LD50 (Rabbit) = 14.4 g/kg Dermal LD50 (Rabbit) = 15,800 mg/kg	Eyes, Irritant, Metabolic, Nervous System

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
2-Propanol	No	No	No
Methanol	No	No	No

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:** D001: Ignitable.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Alcohols, flammable, toxic n.o.s. (Methanol, Isopropanol)

Hazard class or division: 3 (6.1)
Identification number: UN 1986
Packing group: II
DOT Hazardous Substance(s): Methanol

International Air Transportation (ICAO/IATA)

Proper shipping name: Alcohols, flammable, toxic, n.o.s. (Methanol, Isopropanol)

Hazard class or division: 3 (6.1)
Identification number: UN 1986
Packing group: II

IDH number: 510030 Product name: LOCTITE T70 known as T70 THINNER 1GA BOTTLE Page 5 of 6

Water Transportation (IMO/IMDG)

Proper shipping name: ALCOHOLS, FLAMMABLE, TOXIC, N.O.S. (Methanol, Isopropanol)

Hazard class or division: 3 (6.1)
Identification number: UN 1986
Packing group:

## 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health, Delayed Health, Fire

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Methanol (CAS# 67-56-1).

CERCLA Reportable quantity: Methanol (CAS# 67-56-1) 5,000 lbs. (2,270 kg)

California Proposition 65: This product contains a chemical known to the State of California to cause birth defects or

other reproductive harm.

**Canada Regulatory Information** 

IDH number: 510030

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

#### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Product Safety and Regulatory Affairs

**Issue date:** 07/17/2018

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Product name: LOCTITE T70 known as T70 THINNER 1GA BOTTLE Page 6 of 6