



4600 Staticide® Ultra Floor Finish

High Quality, High Performance

No other ESD floor finish can match Staticide® Ultra Floor Finish for electrical properties, physical longevity, and gloss. This urethane-enhanced formula features superior abrasion resistance and durability, fortifying floors with a long-lasting protective layer that is shiny and ESD-safe for 12 to 24 months.

By maximizing stripping cycles, companies can keep costs down by eliminating annual labor fees and production shut-downs.

Staticide® Ultra Floor Finish is the perfect choice for any environment where static control is required, such as electronic, medical, and clean room manufacturing facilities. With an average surface resistivity of 10^8 - 10^9 ohms per square, Staticide® Ultra Floor Finish fulfills ANSI/ESD S20.20 guidelines and is suitable for sensitive device manufacturing.

This water-based formula is UL listed for slip resistance, RoHS compliant, biodegradable, non-flammable, and free of formaldehyde, phthalates, alkalis, acids, and ammonia.

Directions: Clean floor and apply two thin coats of floor finish with a dedicated rayon mop. Wait one hour between coats. Consult application procedure for details and precise instructions.

Maintenance: Sweep or damp mop daily to remove dirt. Periodically clean with a 1:1 dilution of water and floor finish. Apply a thin top coat of floor finish every 4 – 6 weeks. For heavy cleaning, use the 4100 Restorer Cleaner. Consult maintenance procedure for details and precise instructions.

Product #4600-1; 4 gallons per case

Product #4600-5; 5-gallon pail

Product #4600-2; 54-gallon drum

- ❖ **Coverage: 1,500 - 2,000 square feet per gallon**
- ❖ **Non-toxic; biodegradable**
- ❖ **Solids: 20 ± 5%**
- ❖ **Strip cycle: 12-24 months**
- ❖ **Suitable to use on vinyl, linoleum, and ceramic tile**
- ❖ **Surface resistivity: 10^7 – 10^9 ohms per square (average)**
- ❖ **Low V.O.C.**
- ❖ **Water-based acrylic**

