Safety Data Sheet



Revision Number: 006.2

1. PRODUCT AND COMPANY IDENTIFICATION

IDH number:

Product name:

 Product type:
 Liquid

 Restriction of Use:
 None i

 Company address:
 Henkel Corporation

 One Henkel Way
 Rocky Hill, Connecticut 06067

LOCTITE MF R301 known as MFR301 5 GALLON Liquid Flux None identified

Item number:M00473Region:United StatesContact information:Telephone: +1 (860) 571-5100MEDICAL EMERGENCY Phone: Poison Control Center1-877-671-4608 (toll free) or 1-303-592-1711TRANSPORT EMERGENCY Phone: CHEMTREC1-800-424-9300 (toll free) or 1-703-527-3887Internet: www.henkelna.com

511510

2. HAZARDS IDENTIFICATION

	EMERGENCY OVERVIEW
DANGER:	ASPIRATION HAZARD IF SWALLOWED.
	HIGHLY FLAMMABLE LIQUID AND VAPOR.
	MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.
	CAUSES SKIN IRRITATION.
	MAY CAUSE AN ALLERGIC SKIN REACTION.
	CAUSES SERIOUS EYE IRRITATION.
	MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING
	DIFFICULTIES IF INHALED.
	MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	2
SKIN IRRITATION	2
EYE IRRITATION	2A
RESPIRATORY SENSITIZATION	1
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
ASPIRATION HAZARD	1



Precautionary Statements

Prevention:

Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection. In case of inadequate ventilation wear respiratory protection.

Response:	
	IF SWALLOWED: Immediately call a physician or poison control center. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Do NOT induce vomiting. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. If experiencing respiratory symptoms: Call a poison center or physician. Take off contaminated clothing. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.
Storage:	
-	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal:	
	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
2-Propanol	67-63-0	80 - 90	
Hydrocarbon aliphatic aromatic naphthenic C9-12	64742-88-7	10 - 20	
Glutaric acid	110-94-1	1 - 5	
Colophony	8050-09-7	1 - 5	
Adipic acid	124-04-9	1 - 5	

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES		
Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention.	
Skin contact:	Remove contaminated clothing and footwear. Immediately flush skin with plenty of water (using soap, if available). If symptoms develop and persist, get medical attention. Wash clothing before reuse.	
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.	
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.	
Symptoms:	See Section 11.	
Notes to physician:	Aspiration may cause pulmonary edema or aspiration pneumonia.	
	5. FIRE FIGHTING MEASURES	
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.	

Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as
	turn-out gear.

Unusual fire or explosion hazards:

Vapors may form explosive mixtures with air.

Hazardous combustion products:

Oxides of carbon. Thermal decomposition can lead to release of irritating gases and vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

 Environmental precautions:
 Do not allow product to enter sewer or waterways.

 Clean-up methods:
 Ventilate area. Remove all sources of ignition. Evacuate personnel to safe areas. Wear suitable protective clothing, gloves and eye/face protection. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a partly filled, closed container until disposal. Spilled liquid is combustible and can be ignited by heat, flames, sparks, or other sources of ignition. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Keep away from heat, spark and flame. Use only with adequate ventilation. Wear suitable protective clothing, gloves and eye/face protection. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. Empty containers retain product residue, so obey hazard warnings and handle empty containers as if they were full.

Storage:

Handling:

For safe storage, store between 15 °C (59°F) and 30 °C (86°F) Store away from ignition sources. Keep away from heat, spark and flame. Store in original container until ready to use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
2-Propanol	200 ppm TWA 400 ppm STEL	400 ppm (980 mg/m3) PEL	None	None
Hydrocarbon aliphatic aromatic naphthenic C9-12	100 ppm TWA 200 mg/m3 TWA (as total hydrocarbon vapor) Non-aerosol. (SKIN) (as total hydrocarbon vapor) Non-aerosol.	500 ppm (2,900 mg/m3) TWA 100 ppm (400 mg/m3) PEL	None	None
Glutaric acid	None	None	None	None
Colophony	Exposure by all routes should be carefully controlled to levels as low as possible. Included in the regulation but with no data values. See regulation for further details (Respiratory sensitization) (Dermal sensitization)	None	None	None
Adipic acid	5 mg/m3 TWA	None	None	None

Engineering controls:

Use only with adequate ventilation. Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Use NIOSH approved respirator if there is potential to exceed exposure

Respiratory protection:

Eye/face protection:

Skin protection:

Chemical resistant, impermeable gloves.

Safety goggles or safety glasses with side shields.

9. PHYSICAL AND CHEMICAL PROPERTIES

limit(s).

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Flammability: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): **VOC content:** Viscosity: Decomposition temperature:

Liquid Pale yellow Alcoholic Not available. Not determined 6.6 kPa (25 °C (77°F)) 82 °C (179.6 °F) Not determined 0.801 Heavier than air. 14 °C (57.2 °F) Not available. Not available. Not available. Not applicable 2.93 (Butyl acetate = 1) Soluble Not determined 93 %; 744 g/l 1.0 mPa.s Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under recommended storage conditions. Electrostatic charge may build-up during handling. Grounding of equipment is recommended.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Oxides of carbon. Irritating fumes. Formaldehyde.
Incompatible materials:	Incompatible with oxidising agents. Dissolves aluminium and zinc slowly with formation of hydrogen.
Reactivity:	Not available.
Conditions to avoid:	Keep away from open flames, hot surfaces and sources of ignition.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:

Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:	Inhalation of processing fumes may be harmful. May cause allergic respiratory reaction. Vapor overexposure may cause drowsiness. Dizziness. Aspiration may cause lung damage.
Skin contact:	Causes skin irritation. May cause allergic skin reaction.
Eye contact:	Causes serious eye irritation.
Ingestion:	This product may be fatal if it is swallowed. Aspiration may occur during swallowing or vomiting, resulting in lung damage.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
2-Propanol	Oral LD50 (Rat) = 5,045 mg/kg Oral LD50 (Mouse) = 3,600 mg/kg Oral LD50 (Rabbit) = 6,410 mg/kg Oral LD50 (Rat) = 4.7 g/kg Oral LD50 (Mouse) = 4.5 g/kg Oral LD50 (Rabbit) = 8.0 g/kg Oral LD50 (Rabbit) = 5.03 g/kg Dermal LD50 (Rabbit) = 12,800 mg/kg	Allergen, Central nervous system, Irritant
Hydrocarbon aliphatic aromatic naphthenic C9-12	None	Central nervous system, Irritant
Glutaric acid	None	Irritant, Nervous System
Colophony	None	Allergen, Irritant, Respiratory
Adipic acid	Oral LD50 (Mouse) = 1,900 mg/kg Oral LD50 (Rabbit) = > 11,000 mg/kg Oral LD50 (Rat) = > 11,000 mg/kg	Irritant, Kidney, Liver, Nervous System, Respiratory

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
2-Propanol	No	No	No
Hydrocarbon aliphatic aromatic naphthenic C9-12	No	No	No
Glutaric acid	No	No	No
Colophony	No	No	No
Adipic acid	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

13. DISPOSAL CONSIDERATIONS		
Information provided is for unused product only.		
Recommended method of disposal:	Follow all local, state, federal and provincial regulations for disposal.	
Hazardous waste number:	D001: Ignitable.	
14. TF	RANSPORT INFORMATION	
The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.		
U.S. Department of Transportation Ground (49 CFR) Proper shipping name: Flammable liquids, n.o.s. (Isopropanol, Naphtha) Hazard class or division: 3 Identification number: UN 1993 Packing group: II		
International Air Transportation (ICAO/IATA)Proper shipping name:Flammable liquid, n.o.s. (Isopropanol, Naphtha)Hazard class or division:3Identification number:UN 1993Packing group:II		
Water Transportation (IMO/IMDG) Proper shipping name: Hazard class or division: Identification number: Packing group:	FLAMMABLE LIQUID, N.O.S. (Isopropanol, Naphtha) 3 UN 1993 II	

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: TSCA 12 (b) Export Notification:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory. None above reporting de minimis
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis. Immediate Health, Delayed Health, Fire None above reporting de minimis.
California Proposition 65:	This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status:

All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Product Safety and Regulatory Affairs

Issue date: 07/13/2018

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.