

TRANSDUCERIZED SCREWDRIVERS



K-DUCER Transducerized Screwdrivers | Torque range 4.42 – 133 in-lb

K-Ducer is the new A-class intelligent transducerized assembly system from Kolver, the electric tool pioneer since 1989. The system consists of an advanced state-of-the-art controller and a range of handheld and fixtured electric screwdrivers with torque up to 133 in-lb (to be extended to 443 in-lb soon).

Finest accuracy and precision

KDS transducerized electric tools cover all assembly line requirements for an accurate, high-quality torque and angle-controlled tightening experience.

A built-in compact transducer provides torque control with excellent repeatability.

Excellent ergonomics

KDS screwdrivers feature unsurpassed ergonomics, soft touch design, status LED, temperature protection combined with full traceability and error-proofing capabilities.

Available in straight, pistol and fixture configuration.

Connectivity and Industry 4.0

KDS tools are the ideal solution for your Industry 4.0 production line. Built-in LED lights give you immediate feedback on each tightening process, i.e. you'll be able to check at a glance whether the part is correctly tightened or not.

KDS screwdrivers work in combination with KDU control units to gather, analyse and process detailed assembly information.

Their built-in transducer continuously reads torque and position of the screw and sends the gathered data to the KDU controller for analysis.

Available Housings



INLINE (KDS-PL) – Inline versions available in lever start. ESD-safe option available on models KDS-PL /ESD.



PISTOL GRIP – Trigger start, pistol grip available with bottom connector (KDS-PL P). Also available in ESD-safe option (KDS-PL P/ESD).



ALUMINIUM BODY (KDS-PL CA) – Specifically designed for automation. Easy to install on any machine or robot. Version with flange mount available



Inline KDS Screwdrivers

Code	Model	Torque in-lb	RPM min-max	Dimensions in	Weight lb	Bit Drive
135006	KDS-PL6	4.42 - 53	50 - 850	9.9 x 2.0	1.5	Hex 1/4"
135010	KDS-PL10	7.1 - 88.5	50 - 600	9.9 x 2.0	1.5	Hex 1/4"
135015	KDS-PL15	4.42 - 133	50 - 320	9.9 x 2.0	1.5	Hex 1/4"

Pistol grip KDS Screwdrivers

Code	Model	Torque in-lb	RPM min-max	Dimensions in	Weight lb	Bit Drive
135007	KDS-PL6P	4.42 - 53	50 - 850	7.3 x 6.7 x 2	1.5	Hex 1/4"
135011	KDS-PL10P	7.1 - 88.5	50 - 600	7.3 x 6.7 x 2	1.5	Hex 1/4"
135016	KDS-PL15P	4.42 - 133	50 - 320	7.3 x 6.7 x 2	1.5	Hex 1/4"

Inline KDS Screwdrivers in ESD-safe housing

Code	Model	Torque in-lb	RPM min-max	Dimensions in	Weight lb	Bit Drive
135006/ESD	KDS-PL6/ESD	4.42 - 53	50 - 850	9.9 x 2.0	1.5	Hex 1/4"
135010/ESD	KDS-PL10/ESD	7.1 - 88.5	50 - 600	9.9 x 2.0	1.5	Hex 1/4"
135015/ESD	KDS-PL15/ESD	4.42 - 133	50 - 320	9.9 x 2.0	1.5	Hex 1/4"

Pistol grip KDS Screwdrivers in ESD-safe housing

Code	Model	Torque in-lb	RPM min-max	Dimensions in	Weight lb	Bit Drive
135007/ESD	KDS-PL6P/ESD	4.42 - 53	50 - 850	7.3 x 6.7 x 2	1.5	Hex 1/4"
135011/ESD	KDS-PL10P/ESD	7.1 - 88.5	50 - 600	7.3 x 6.7 x 2	1.5	Hex 1/4"
135016/ESD	KDS-PL15P/ESD	4.42 - 133	50 - 320	7.3 x 6.7 x 2	1.5	Hex 1/4"

Aluminium housing KDS Screwdrivers

Code	Model	Torque in-lb	RPM min-max	Dimensions in	Weight lb	Bit Drive
135106	KDS-PL6CA	4.42 - 53	50 - 850	9.8 x 1.6	1.9	Hex 1/4"
135110	KDS-PL10CA	7.1 - 88.5	50 - 600	9.8 x 1.6	1.9	Hex 1/4"
135115	KDS-PL15CA	4.42 - 133	50 - 320	9.8 x 1.6	1.9	Hex 1/4"

Aluminium housing KDS Screwdrivers with flange mount

Code	Model	Torque in-lb	RPM min-max	Dimensions in	Weight lb	Bit Drive
135106/FN	KDS-PL6CA/FN	4.42 - 53	50 - 850	13.8 x 1.6	2.4	Sq 3/8"
135110/FN	KDS-PL10CA/FN	7.1 - 88.5	50 - 600	13.8 x 1.6	2.4	Sq 3/8"
135115/FN	KDS-PL15CA/FN	4.42 - 133	50 - 320	13.8 x 1.6	2.4	Sq 3/8"

IMPORTANT: Continuous use over 80% of torque range is not recommended.

KDS Screwdrivers work in combination with KDU series controllers. See page 10 for further information.



KDU-1 Controllers | K-Ducer Power Units

The KDU-1 Series of controllers give you full control of your fastening operation in an industry leading compact size.

Features

With features like touch screen color display, multiple programs and sequences, intuitive programming interface, torque and angle control and graphs output, the KDU-1 units provide unmatched performance and value.

Easy to use

Set-up and operation are really an easy task. Units may be programmed either through the touch screen or via a PC software.

Different models, plenty of options

The power unit comes in two versions depending on the functionality level required.

The KDU-1 basic unit includes serial and USB ports.

In addition to that, KDU-1A advanced controllers feature a Modbus TCP communication port.

Most communication protocols are available with the support of external modules. Wi-fi is also an additional option.

KDU controllers will operate all KDS series of tools.

Connectivity and Industry 4.0

Industry 4.0 – The Fourth Industrial Revolution – is driving the evolution of the assembly process. The digitalization of manufacturing and assembly means shifting the way we look at manufacturing in terms of production optimization and automation.

The more informed you are, the better decisions you can make. Having smart tools on your line means that you have specific tightening information fed into the production system – information concerning critical details of your components, materials and tightening process.

This provides a valuable opportunity to increase efficiency and results in pro-active problem solving, alongside with considerable energy savings from efficiency improvements.

Optional supports

A table stand or wall mount are available for KDU units.

Wall mounts can be easily installed on any vertical surface and allow KDU controllers to tilt up/down and left/right – place your KDU unit anywhere and adjust its position to best suit your needs.

A table stand ensures quick access to cables when placing your KDU unit on a flat surface. It is the best option in case you'd like to keep your KDU controller right at hand.





Table Stand



Wall Bracket

Supports for KDU control units

Code	Model	Description
010400	Table stand	For table use
010401	Wall mount tilting bracket	For wall or column use



Controllers for Transducerized Screwdrivers / K-DUCER Series


Features	KDU-1 Basic	KDU-1A Advanced
5" Touch Screen	•	•
Number of programs	64	64
Sequences	8	8
20 Input NPN	•	•
21 Outputs	•	•
Torque graph	•	•
Bar code reading	•	•
Torque & angle control	•	•
Multiple parameters	•	•
RS 232 (2)	•	•
Mini USB	•	•
USB	•	•
Modbus TCP		•
Devicenet		+
CC-Link		+
Profibus		+
Ethernet / IP		+
Profinet		+
Profinet FO		+
Ethercat		+
CC-Link IE Field		+
Powerlink		+

+ = available as a separate module interface to Modbus




Cables | K-Ducer Screwdrivers and Control Units

Cables are required to complete any K-Ducer system, as they connect KDS screwdrivers to KDU control units. They're made of sturdy materials to guarantee exceptional resistance to wear and tear. Also, they're superquick to connect thanks to their one-click connector. Two different lengths (98 in and 197 in) are available to meet any production requirement.



Driver connector (KDS view)



Unit connector (KDU view)

Cables to connect KDS screwdrivers to KDU units

Code	Model	Description
250064	Cable 98 in	M16 10pin 98 in
250064/H	Cable 98 in, heavy duty	M16 10pin 98 in
250564	Cable 197 in	M16 10pin 197 in
250564/H	Cable 197 in, heavy duty	M16 10pin 197 in